

# Sustainability data sheet

## ARDEX A 35 MIX Rapid-hardening-cement MIX

Solid and liquid construction. Ready for coating after 24 hours. Quickly viable. With ARDURAPID effect.

### Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

**EMICODE® EC 1<sup>PLUS</sup> R,**  
very low emission



According Emission Classification of Building Materials

-

solvent-free

### EPD (Environmental Product Declaration)

ARDEX A 35 MIX corresponds to FEICA EPD:

**EPD-FEI-20160017-IBG1-EN**

### According BASTA

ARDEX A 35 MIX is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See [www.bastaonline.se](http://www.bastaonline.se)



### Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE ZP1** - cementitious product, low-chromate

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)



# ARDEX A 35 MIX

Rapid-hardening-cement MIX

## Sustainable Building

### Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

#### Version 2018

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX A 35 MIX is no evaluation-relevant product according DGNB.

ARDEX A 35 MIX has the GISOCDE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV.

**ARDEX A 35 MIX fulfills the requirements for highest Quality Level 4.**

#### Version 2015

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX A 35 MIX is no evaluation-relevant product according DGNB.

ARDEX A 35 MIX has the GISOCDE ZP1 and is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV.

**ARDEX A 35 MIX fulfills the requirements for highest Quality Level 4.**

### Accordinging LEED (Leadership in Energy and Environmental Design)

#### Version 4 (2014)

##### EQ: Low Emitting Materials

ARDEX A 35 MIX meets the requirements according EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV which are accepted by LEED.

**ARDEX A 35 MIX meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.**

##### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX A 35 MIX corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX A 35 MIX fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

#### Version 2009

##### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

Cement based renders are not directly described by LEED. But the permitted limit value in the category coatings is 50 g/L. The VOC value of ARDEX A 35 MIX is < 50 g/L.

**ARDEX A 35 MIX meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

##### MR Credit 5.1 und 5.2: Regional Materials

###### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



# ARDEX A 35 MIX

Rapid-hardening-cement MIX

## Sustainable Building

### According BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

#### Version 2016

#### BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX A 35 MIX fulfills the required emission limits and is certified by EMICODE® EC 1<sup>PLUS</sup> R, very low emission, based on GEV which is accepted as documentation.

**ARDEX A 35 MIX meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.**

### According Nordic Swan Ecolabelling

**ARDEX A 35 MIX is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings.**

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 10/01/2019

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)

