

# Sustainability data sheet

## ARDEX P 2 D

### Liquid vapor barrier

For steam blocking layer under wet membrane. Approved according to ETAG 022.  
Ready to use, fast Drying, Water vapour resistance 1.44 million s/m, solvent-free.

#### Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

-

According Emission Classification of Building Materials

**M1**



solvent-free

#### EPD (Environmental Product Declaration)

ARDEX P 2 D corresponds to FEICA EPD:

**EPD-FEI-20160086-IBG1-EN**

#### According BASTA

ARDEX P 2 D is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See [www.bastaonline.se](http://www.bastaonline.se)



#### Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE D1** – solvent-free dispersion installation products

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)



# ARDEX P 2 D

Liquid vapor barrier

## Sustainable Building

### Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

#### Version 2018

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX P 2 D can be classified as coatings on mainly mineral surfaces in the interior such as trowels (also Dispersion filler) as well as wallpapers, fleeces, Plasterboards etc. Floor surfaces with special resistance requirements (like OS systems), underground parking and driveways are not considered (incl. Q-trowel).

Notice: For products up to 5 % of BGFa (DIN 277) no documentation is required.

ARDEX P 2 D is water-dilutable according Decopaint-RL.

**ARDEX P 2 D fulfills the requirements for Quality Level 1.**

#### Version 2015

##### DGNB criteria ENV 1.2: Local environmental impact

ARDEX P 2 D can be classified as coatings on mainly mineral surfaces in the interior such as trowels (also Dispersion filler) as well as wallpapers, fleeces, Plasterboards etc. Floor surfaces with special resistance requirements (like OS systems), underground parking and driveways are not considered (incl. Q-trowel).

Notice: For products up to 5 % of BGFa (DIN 277) no documentation is required.

ARDEX P 2 D is water-dilutable according Decopaint-RL.

**ARDEX P 2 D fulfills the requirements for Quality Level 1.**

### Accordinging LEED (Leadership in Energy and Environmental Design)

#### Version 4 (2014)

##### EQ: Low Emitting Materials

ARDEX P 2 D does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

**ARDEX P 2 D does not meet the requirements.**

##### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX P 2 D corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX P 2 D fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

#### Version 2009

##### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX P 2 D according SCAQMD Rule 1168 is < 65 g/L.

**ARDEX P 2 D meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

##### MR Credit 5.1 und 5.2: Regional Materials

###### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
www.ardex.de

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
kundendienst@ardex.de  
www.ardex.de



# ARDEX P 2 D

Liquid vapor barrier

## Sustainable Building

According BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

### Version 2016

#### BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX P 2 D is certified by M1 which is accepted as documentation.

**ARDEX P 2 D meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.**

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship.

Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 18/04/2018

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

